


| | |
|-----------------------------------------------------------------------------------------------------------------------------|--------|
|  1235 | |
| Idealcombi A/S Noerre Allé 51, 7760 Hurup Thy Denmark 13 518/CPR/2013-06-27 | |
| EN 14351-1:2006+A1:2010 | |
| External pedestrian doors – Product: Futura+ (28 mm glazing) Outward opening doors | |
| Intended for use in domestic and commercial locations | |
| Wind load resistance: | npd |
| Watertightness – Non-shielded(A): | npd |
| Height: | npd |
| Dangerous substances: | None |
| Load-bearing capacity of safety devices: | - |
| Acoustic performance: | npd |
| Thermal transmittance (U_D -value): | |
| - Outw. opening door 1230 x 2180 mm with 1 no. std. glazing | 1,31** |
| - Outw. opening sliding door 2500 x 2180 mm with 2 no. std. glazing | 1,36** |
| Radiation properties – Solar factor (g) : | 0,73 |
| Radiation properties – Light transmittance (τ_v) : | 0,81 |
| Impact resistance: | npd |
| Air permeability: | npd |
| npd: no performance determined | |

**Regarding the thermal transmittance of actual doors, we refer to quotations and order confirmations cf. EN 14351-1:2006+A1:2010, Table E.2 note d.