

DECLARATION OF PERFORMANCE

DoP-no. 507/CPR/2014-08-07

| 1. Unique identification code of the product type: | | |
|---|--|--|
| Windows | | |
| 2. Identification of the construction product: | | |
| Contura Frame | | |
| 3. Intended use of the construction product: | | |
| Domestic and commercial locations | | |
| 4. Name and contact address of the manufacturer: | | |
| IdealCombi A/S, | | |
| Noerre Allé 51, 7760 Hurup Thy | | |
| Denmark | | |
| Phone no. +45 96 88 25 00 | | |
| Fax no. +45 97 95 14 09 | | |
| E-mail: info@idealcombi.dk | | |
| 5. Name and contact address of authorised representative: | | |
| n/a | | |
| 6. Systems of assessment and verification of constancy of performance of the construction product (AVCP): | | |
| System 3 | | |
| 7. Harmonised standard and notified body/bodies: | | |

EN 14351-1:2006 + A1:2010

Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets without resistance to fire and/or smoke leakage characteristics

Danish Technological Institute, NB-no. 1235

has performed

Calculation of thermal transmittance

according to system

System 3, type calculation

and issued:

Test report nr. 0108/415307

8. Declared performance

| Essential characteristics | Performance | Harmonised technical specification |
|--|--|------------------------------------|
| Resistance to wind load | npd | |
| Watertightness – Non-shielded(A) | npd | |
| Dangerous substances | None | |
| Load-bearing capacity of safety | - | |
| devices | | |
| Acoustic performance | npd | |
| Thermal transmittance | Inward opening window with std. glazing $U_w = 1,43 \text{ W/m}^2\text{K} (1230x1480 \text{ mm})$ Fixed light with std. glazing $U_w = 1,39 \text{ W/m}^2\text{K} (1230x1480 \text{ mm})$ Inw. opening door height window with 2 no. std. glazings $U_w = 1,46 \text{ W/m}^2\text{K} (1230x2180 \text{ mm})$ | EN 14351-1:2006 + A1:2010 |
| Radiation properties – Solar factor | g = 0.72 | |
| Radiation properties – Light transmittance | $\tau_{\rm V} = 0.80$ | |
| Air permeability | npd | |

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

| Signed for and on behalf of the manufacturer by: | | | |
|--|--------------|--|--|
| Technical Director | Bent Søgaard | | |
| Hurup, 2014-08-07 | | | |
| | | | |