

## **DECLARATION OF PERFORMANCE**

DoP-no. 531/CPR/2020-11-25

1. Unique identification code of the product type:			
Windows			
2. Identification of the construction product:			
NATION IC 28			
3. Intended use of the construction product:			
Domestic and commercial locations			
4. Name and contact address of the manufacturer:			
IdealCombi A/S,			
Noerre Allé 51, 7760 Hurup Thy			
Denmark			
Phone no. +45 96 88 25 00			
Fax no. +45 97 95 14 09			
E-mail: info@idealcombi.dk			
5. Name and contact address of authorised representative:			
n/a			
6. Systems of assessment and verification of constancy of performance of the construction product (AVCP):			
System 3			
7. Harmonised standard and notified body/bodies:			

Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

EN 14351-1:2006 + A2:2016

DoP 531/CPR/2020-11-25 Page 1 of 3

Danish Technological Institute, NB-no. 1235

has performed

Test of load-bearing capacity of safety devices

Calculation of thermal transmittance

according to system

System 3, type testing and type calculation

and issued:

Test report no. 0301/631571-TV2 – test of load-bearing capacity of safety devices

Test report no. 0108/640522 – calculation of thermal transmittance

## 8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Resistance to wind load	npd	
Watertightness - Non-shielded(A)	npd	
Dangerous substances	None	
Load-bearing capacity of safety	Pass	
devices (reversible window)		
Acoustic performance	npd	
Thermal transmittance	Single casement window with std. glazing $U_w = 1,32 \text{ W/m}^2\text{K} (1230x1480 \text{ mm})$ Fixed light with std. glazing $U_w = 1,30 \text{ W/m}^2\text{K} (1230x1480 \text{ mm})$	EN 14351-1:2006 + A2:2016
Radiation properties – Solar factor	g = 0.73	
Radiation properties – Light	$\tau_{\rm V} = 0.80$	
transmittance		
Air permeability	npd	

performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Technical Director Mikael Søgaard

Hurup, 2020-11-25

9. The performance of the product identified in points 1 and 2 is in conformity with the declared