

Declaration of performance

DoP-no. 323/CPR/2018-05-16

Unique identification code of the product type:
FUTURA+ I 28 – Fixed and inward opening windows

Intended use:
Domestic and commercial locations

Manufacturer:
Idealcombi A/S,
Noerre Allé 51, 7760 Hurup Thy
Denmark
Phone no. +45 96 88 25 00
Fax no. +45 97 95 14 09
E-mail: info@idealcombi.dk

Authorised representative:
n/a

System of AVCP:
System 3

Harmonised standard:
EN 14351-1:2006 + A2:2016
Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Notified body:
Danish Technological Institute, NB-no. 1235

Appropriate Technical Documentation and/or Specific Technical Documentation:
n/a

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Hurup, 2018-05-16

Technical Director Mikael Søgaard



Declaration of performance
DoP-no. 323/CPR/2018-05-16
FUTURA+ I 28 – Fixed and inward opening windows



Declared performance:

		Resistance to wind load	Watertightness - Non-shielded (A)	Dangerous substances	Load-bearing capacity of safety devices (reversible window)	Acoustic performance	Thermal transmittance, U [W/m ² K]	Radiation properties		Air permeability
								Solar factor, g	Light transmittance, τ_v	
Tilt-turn window Inward opening window with std. glazing	Performance	C4	E1800	None	-	npd	1,38	0,73	0,82	4
	Test size [mm]	1150 x 2600	1150 x 2600				1230 x 1480			1150 x 2600
	Notified body	no. 1235	no. 1235				no. 1235			no. 1235
	Test report no.	0301/ 810143r1-TT	0301/ 810143r1-TT				0108/748187			0301/ 810143r1-TT
Fixed light window Fixed light window with std. glazing	Performance	C4	E1800	None	-	npd	1,38	0,73	0,82	4
	Test size [mm]	1150 x 2600	1150 x 2600				1230 x 1480			1150 x 2600
	Notified body	no. 1235	no. 1235				no. 1235			no. 1235
	Test report no.	0301/ 810143r1-TT	0301/ 810143r1-TT				0108/748187			0301/ 810143r1-TT