

## Declaration of performance

DoP-no. 336/CPR/2019-03-11

Unique identification code of the product type:  
FUTURA+ 44 – Fixed and outward opening windows

Intended use:  
Domestic and commercial locations

Manufacturer:  
Idealcombi A/S,  
Noerre Allé 51, 7760 Hurup Thy  
Denmark  
Phone no. +45 96 88 25 00  
Fax no. +45 97 95 14 09  
E-mail: info@idealcombi.dk

Authorised representative:  
n/a

System of AVCP:  
System 3

Harmonised standard:  
EN 14351-1:2006 + A2:2016  
Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Notified bodies:  
Danish Technological Institute, NB-no. 1235

Appropriate Technical Documentation and/or Specific Technical Documentation:  
n/a

The performance of the product identified above is in conformity with the set of declared performance/s.  
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Hurup, 2019-03-11

Technical Director Mikael Søgaard



Declaration of performance  
DoP-no. 336/CPR/2019-03-11  
FUTURA+ 44 – Fixed and outward opening windows



Declared performance:

		Resistance to wind load	Watertightness - Non-shielded (A)	Dangerous substances	Load-bearing capacity of safety devices (reversible window)	Acoustic performance	Thermal transmittance, $U_w$ [W/m <sup>2</sup> K]	Radiation properties		Air permeability
								Solar factor, g	Light transmittance, $\tau_v$	
Top guided window Single outward opening top guided window with std. glazing	Performance	npd	E1800	None	-	npd	0,78	0,62	0,75	npd
	Test size [mm]		1600 x 1588				1230 x 1480			
	Notified body		no. 1235				no. 1235			
	Test report no.		0301/557297				0108/737572			
Side hung window Single outward opening side hung window with std. glazing	Performance	npd	E1500	None	-	npd	0,78	0,62	0,75	npd
	Test size [mm]		1150 x 2400				1230 x 1480			
	Notified body		no. 1235				no. 1235			
	Test report no.		1321521				0108/737572			
Side guided window Single outward opening side guided window with std. glazing	Performance	npd	E1800	None	-	npd	0,78	0,62	0,75	npd
	Test size [mm]		1600 x 1588				1230 x 1480			
	Notified body		no. 1235				no. 1235			
	Test report no.		0301/557297				0108/737572			
Reversible window Single reversible window with std. glazing	Performance	npd	E1500	None	350 N, 60 sek.	npd	0,86	0,62	0,75	npd
	Test size [mm]		1600 x 1588		-		1230 x 1480			
	Notified body		no. 1235		no. 1235		no. 1235			
	Test report no.		1325568		1319514		0108/737572			
Fixed light window Single fixed light window with std. glazing	Performance	npd	E1500	None	-	npd	0,78	0,62	0,75	npd
	Test size [mm]		1150 x 2400				1230 x 1480			
	Notified body		no. 1235				no. 1235			
	Test report no.		1321521				0108/737572			