



DECLARATION OF PERFORMANCE

DoP-no. 335/CPR/2017-01-20

1. Unique identification code of the product type:

FUTURA+ 30 – Fixed and outward opening windows

2. Intended use:

Domestic and commercial locations

3. Manufacturer:

Idealcombi A/S,
Noerre Allé 51, 7760 Hurup Thy
Denmark

Tlf. +45 96 88 25 00
Fax nr. +45 97 95 14 09
E-mail: info@idealcombi.dk

4. Authorised representative:

n/a

5. System of AVCP:

System 3

6. Harmonised standard:

EN 14351-1:2006 + A2:2016

Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Notified body:

Danish Technological Institute, NB-no. 1235

Has performed tests for:

7. Declared performance:

| Essential characteristics | Performance |
|---|---|
| Resistance to wind load | C4 |
| Watertightness - Non-shielded (A) | E1500 |
| Dangerous substances | None |
| Load-bearing capacity of safety devices (reversible window) | Pass |
| Acoustic performance | npd |
| Thermal transmittance | Single casement window with std. glazing $U_w = 1,31 \text{ W/m}^2\text{K}$ (1230x1480 mm) Reversible window with std. glazing $U_w = 1,38 \text{ W/m}^2\text{K}$ (1230x1480 mm) Fixed light with std. glazing $U_w = 1,31 \text{ W/m}^2\text{K}$ (1230x1480 mm) |
| Radiation properties - Solar factor | $g = 0,73$ |
| Radiation properties - Light transmittance | $\tau_v = 0,82$ |
| Air permeability | 4 |

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

n/a

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Technical Director Mikael Søgaard

Hurup, 2017-01-20

.....