



DECLARATION OF PERFORMANCE

DoP-no. 339/CPR/2017-01-20

1. Unique identification code of the product type:

FUTURA+ 30 – Outward opening sliding doors

2. Intended use:

Domestic and commercial locations

3. Manufacturer:

Idealcombi A/S,
Noerre Allé 51, 7760 Hurup Thy
Denmark

Tlf. +45 96 88 25 00
Fax nr. +45 97 95 14 09
E-mail: info@idealcombi.dk

4. Authorised representative:

n/a

5. System of AVCP:

System 3

6. Harmonised standard:

EN 14351-1:2006 + A2:2016

Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Notified body:

Danish Technological Institute, NB-no. 1235

Has performed tests for:

7. Declared performance:

Essential characteristics	Performance
Resistance to wind load	C3
Watertightness - Non-shielded (A)	E1500
Dangerous substances	None
Load-bearing capacity of safety devices (reversible window)	-
Height	npd
Acoustic performance	npd
Thermal transmittance	Outw. opening sliding door with 2 no. std. glazing $U_D = 1,36 \text{ W/m}^2\text{K}$ (2500x2180 mm) Outw. opening sliding door with low threshold with 2 no. std. glazing $U_D = 1,13 \text{ W/m}^2\text{K}$ (2500x2180 mm)
Radiation properties - Solar factor	$g = 0,73$ $g = 0,62$ Outw. opening sliding door with low threshold, 44 mm glazing fixed part
Radiation properties - Light transmittance	$\tau_v = 0,82$ $\tau_v = 0,75$ Outw. opening sliding door with low threshold, 44 mm glazing fixed part
Air permeability	4

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

n/a

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Technical Director Mikael Sogaard

Hurup, 2017-01-20

.....

.....