

Declaration of performance

DoP-no. 341/CPR/2018-04-09

Unique identification code of the product type:
IC Sliding door (28/48) – Outward opening sliding door

Intended use:
Domestic and commercial locations

Manufacturer:
Idealcombi A/S,
Noerre Allé 51, 7760 Hurup Thy
Denmark
Phone no. +45 96 88 25 00
Fax no. +45 97 95 14 09
E-mail: info@idealcombi.dk

Authorised representative:
n/a

System of AVCP:
System 3

Harmonised standard:
EN 14351-1:2006 + A2:2016
Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Notified body:
Danish Technological Institute, NB-no. 1235

Appropriate Technical Documentation and/or Specific Technical Documentation:
n/a

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Hurup, 2018-04-09

Technical Director Mikael Søgaard



Declaration of performance
DoP-no. 341/CPR/2018-04-09
IC Sliding door (28/48) – Outward opening sliding door



Declared performance:

| | | Resistance to wind load | Watertightness - Non-shielded (A) | Dangerous substances | Load-bearing capacity of safety devices (reversible window) | Height | Acoustic performance | Thermal transmittance, U [W/m ² K] | Radiation properties | | Air permeability |
|--|-----------------|-------------------------|-----------------------------------|----------------------|---|--------|----------------------|---|----------------------|-------------------------------|------------------|
| | | | | | | | | | Solar factor, g | Light transmittance, τ_v | |
| Sliding door | Performance | npd | npd | None | - | npd | npd | 1,18 | 0,73* /0,62** | 0,82* /0,75** | npd |
| Outward opening sliding door with 2 no. std. glazing | Test size [mm] | | | | | | | 2500 x 2180 | | | |
| | Notified body | | | | | | | no. 1235 | | | |
| | Test report no. | | | | | | | 0108/803935 | | | |

*28 mm glazing - fixed part

**48 mm glazing - fixed part