


|                                                                                   |        |
|-----------------------------------------------------------------------------------|--------|
|  |        |
| Idealcombi A/S<br>Noerre Allé 51, 7760 Hurup Thy<br>Denmark<br>12                 |        |
| EN 14351-1:2006+A1:2010                                                           |        |
| Windows – Product: <b>futura</b>                                                  |        |
| Designed for use in buildings                                                     |        |
| Wind load:                                                                        | npd    |
| Watertightness:                                                                   | npd    |
| Load-bearing capacity of safety devices<br>(reversible window):                   | Passed |
| Acoustic performance:                                                             | npd    |
| Thermal transmittance ( $U_w$ -value):                                            |        |
| - Single casement window 1230 x 1480 mm with std. glazing                         | 1,6*   |
| - Fixed light 1230 x 1480 mm with std. glazing:                                   | 1,6*   |
| Air permeability:                                                                 | npd    |
| Radiation properties – Solar factor (g) :                                         | 0,61   |
| Radiation properties – Light transmittance ( $\tau_v$ ) :                         | 0,80   |
| npd: no performance determined                                                    |        |

\*Regarding the thermal transmittance of actual windows, we refer to quotations and order confirmations cf. EN 14351-1:2006+A1:2010, Table E.1 note c.