

 1235	
Idealcombi A/S Noerre Allé 51, 7760 Hurup Thy Denmark 14 517/CPR/2014-08-07	
EN 14351-1:2006+A1:2010	
Windows – Product: Futura+ (38 mm glazing) Outward opening windows and fixed lights	
Intended for use in domestic and commercial locations	
Wind load resistance:	npd
Watertightness – Non-shielded(A):	npd
Dangerous substances:	None
Load-bearing capacity of safety devices: (reversible window)	Pass
Acoustic performance:	npd
Thermal transmittance (U_w -value):	
- Single casement window 1230 x 1480 mm with std. glazing	0,87*
- Reversible window 1230 x 1480 mm with std. glazing	0,96*
- Fixed light 1230 x 1480 mm with std. glazing	0,87*
- Outward opening door height window 1230 x 2180 mm with 1 no. std. glazing and horizontal spacer bar	0,87*
- Outward opening sliding door with low threshold 2500 x 2180 mm with 2 no. std. glazing	0,94*
Radiation properties – Solar factor (g) :	0,63
Radiation properties – Light transmittance (τ_v) :	0,74
- Outward opening sliding door with low threshold, 42 mm glazing fixed part (τ_v) :	0,73
Air permeability:	npd
npd: no performance determined	

*Regarding the thermal transmittance of actual windows, we refer to quotations and order confirmations cf. EN 14351-1:2006+A1:2010, Table E.1 note c.