


|   |       |
|---|-------|
| <br>1235       |       |
| Idealcombi A/S<br>Noerre Allé 51, 7760 Hurup Thy<br>Denmark<br><br>16<br><br>528/CPR/2016-02-16 |       |
| EN 14351-1:2006+A1:2010   |       |
| Windows – Product:<br>FRAME IC 48   |       |
| Intended for use in domestic and commercial locations   |       |
| Wind load resistance:   | npd   |
| Watertightness – Non-shielded(A):   | npd   |
| Dangerous substances:   | None  |
| Load-bearing capacity of safety devices:<br>(reversible window)                                 | Pass  |
| Acoustic performance:   | npd   |
| Thermal transmittance (U <sub>w</sub> -value):  |       |
| - Single casement window 1230 x 1480 mm with std. glazing                                       | 0,84* |
| - Fixed light 1230 x 1480 mm with std. glazing  | 0,75* |
| Radiation properties – Solar factor (g) :   | 0,63  |
| Radiation properties – Light transmittance (τ <sub>v</sub> ) :                                  | 0,73  |
| Air permeability:   | npd   |
| npd: no performance determined  |       |

\*Regarding the thermal transmittance of actual windows, we refer to quotations and order confirmations cf. EN 14351-1:2006+A1:2010, Table E.1 note c.